

TECHNICAL DATA SHEET

Name

Code

OMEGA NEOS S1P

6918N S1P SRC

Product Range

Standard

EN ISO

Weight

Size range

Mondopoint

Packaging



S1P SRC

20345:2011

680 grams
(1 shoe in size 42)

35 <-> 50

10,5

10 pairs/carton
(same size)

TECHNICAL SPECIFICATIONS



SOLE

SOLE FEATURES



DOUBLE FORMULA® soles feature a morpho-anatomical design, blending light, flexible PU foam midsoles with durable, grippy outsoles made of compact PU.



PROTECTIVE ELEMENTS

UPPER

LINING

FOOTBED



Heat-treated and epoxy-coated safety toe cap withstands impacts up to 200 Joules and compressions up to 15 kN. Stainless steel fibers increase durability and beveled edges enhance comfort.



Corrosion-resistant steel plate integrated into the outsole, protecting the foot from penetration by foreign objects.



Premium leather with a thick-grain finish, specially tanned for flexibility, durability, and adaptability in any work environment.



Three-layer wear-resistant lining featuring a microchannel network for unparalleled breathability and antimicrobial properties to prevent odors and microorganism growth.



Antistatic and anti-odour removable insole with SANITIZED® technology ensuring hygiene and a fresh feeling all day.

EXTRA



SAFETY TECHNICAL SPECIFICATIONS

| Description | Measurement Unit | Requirement | Test Result |
|---|------------------|-------------|-------------|
| TOE CAP: Impact resistance | mm | ≥ 14 | 14 |
| TOE CAP: Compression resistance | mm | ≥ 14 | 18 |
| ANTI-PUNCTURE PLATE: Penetration resistance | N | ≥ 1.100 | 1384 |
| FOOTWEAR: Antistatic properties (in wet condition) | MΩ | ≥ 0,1 | 41 |
| FOOTWEAR: Antistatic properties (in dry condition) | MΩ | ≤ 1.000 | 560 |
| UPPER: Water vapour permeability | mg/cm2*h | ≥ 0,8 | 2,5 |
| UPPER: Water vapour coefficient | mg/cm2 | ≥ 15 | 27 |
| UPPER: Water penetration after 60 min | g | ≤ 0,2 | - |
| UPPER: Water absorption after 60 min | % | ≤ 30 | - |
| INTERNAL LINING: Water vapour permeability | mg/(cm2*h) | ≥ 2,0 | 130,7 |
| INTERNAL LINING: Water vapour coefficient | mg/cm2 | ≥ 20 | 1045,8 |
| OUTSOLE: Abrasion resistance | mm3 | ≤ 150 | 54 |
| OUTSOLE: Energy absorption of seat region (E) | J | ≥ 20 | 38 |
| OUTSOLE: Flexural resistance | mm | ≤ 4 | 1 |
| OUTSOLE: Interlayer bond strength | N/mm | ≥ 4 | 3,6 |
| OUTSOLE: Resistance to fuel oil (FO) | % | ≤ 12 | 2,7 |

ADDITIONAL FEATURES

| Test | Measurement Unit | Requirement | Results |
|--|------------------|--|---------|
| Electrical resistance for ESD footwear <small>Requirements IEC 61340-5-1:2016</small> | mA | ≤ 1,00 | - |
| Resistance to hot contact (HRO) | - | outsoles shall not melt and develop any cracks when bent | - |
| Cold insulation of outsole complex (CI) 30min/-17°C <small>(temperature decrease on the upper surface of the insock)</small> | °C | ≤ 10 | - |
| Heat insulation of outsole complex (HI) 30min/150°C | °C | ≤ 22 | - |
| Water resistance (WR) <small>(Total wetted area inside the footwear)</small> | cm2 | after 80 min. | - |
| Electric hazard resistance (EH) 18kV / 60 Hz <small>(Electric flux)</small> | MΩ | ≤ 100 | - |

STORAGE, CARE AND MAINTENANCE

- PANDA SAFETY footwear should be stored in original packaging, storage temperature should not exceed 35°C, humidity should be less than 80% and without the influence of direct sunlight.
- Sandals, shoes and boots should be cleaned after each use; dry off the shoes, not in proximity to or in direct contact with stoves or other sources of heat.
- Carry out the periodic treatment of the uppers with suitable products containing wax, grease, silicone, etc.
- Avoid contact with aggressive chemicals and extreme temperatures.
- Verify the good state before each use.

SOLE DESIGN AND PERFORMANCE



ENERGY ABSORPTION COEFFICIENT IN THE HEEL AREA



INDUSTRIES

